

Bibliography

- M. Beck and T. Hirschfeld, "Apparatus including optical fiber for fluorescence immunoassay," US Patent #4,582,809 (April 15, 1986).
- M. A. Belkerdid, N. Ghandeharioun, and B. Brennan, "Fiber optic fluid level sensor," *Proc. SPIE* **566**, 153–158 (1986) [doi: 10.1117/12.949781].
- J. W. Berthold et al., "Design and Characterization of a High Temperature Fiber-Optic Pressure Transducer," *J. Lightwave Technol.* **5**(7), 870 (1987).
- T. Bosselmann et al., "Fiber optic temperature sensor using fluorescence decay time," *Proc. SPIE* **514**, 151 (1984) [doi: 10.1117/12.945072].
- W. K. Burns, ed., *Optical Fiber Rotation Sensing*, Academic Press, Boston (1994).
- B. A. Childers et al., "Fiber optic position and shape sensing device and method relating thereto," US Patent Application Publication 2007/0065077 (2007).
- R. Claus and R. S. Rogowski, eds., *Fiber Optic Smart Structures and Skins V*, *Proc. SPIE* **1798** (1992).
- B. Culshaw and J. Dakin, eds., *Optical Fibre Sensors*, Vols. I, II, III, and IV, Artech House, Boston (1988–1996).
- R. R. Dils, "Optical Fiber Thermometer," US Patent #4,576,486 (May 18, 1986).
- H. H. Du, G. Pickrell, E. Udd, C. S. Baldwin, J. J. Benterou, and A. Wang, eds., *Fiber Optic Sensors and Applications XI*, *Proc. SPIE* **9098** (2014).
- R. DePaula and J. Berthold, eds., *Fiber Optic and Laser Sensors XIV*, *Proc. SPIE* **2839** (1996).
- B. Glisic and D. Inaudi, *Fibre Optic Methods for Structural Monitoring*, John Wiley & Sons, New York (2007).
- M. C. Hutley, *Diffraction Gratings*, Academic Press, London (1982).

Bibliography

A. D. Kersey, "A Review of Recent Developments in Fiber Optic Sensor Technology," *Opt. Fiber Technol.* **2** (3), 291–317 (1996).

R. H. Kingston, *Detection of Optical and Infrared Radiation*, Springer-Verlag, Berlin (1978).

G. Kirchhoff, "On the relation between the radiating and absorbing powers of different bodies for light and heat," *Annalen der Physik* **109**, 275 (1860).

C. D. Kissinger, "Fiber optic proximity probe," US Patent #3,327,584 (June 27, 1967).

R. D. LaClair, W. B. Spillman, Jr., and W. W. Kuhns, "Long stroke optical fiber linear position sensor for the FLASH program," *Proc. SPIE* **2840**, 137–141 (1996) [doi: 10.1117/12.254223].

N. Lagakos et al., "Microbend fiber-optic sensor," *Appl. Opt.* **26**(11), 2171 (1987).

W. R. Lawrence, "Fiber optic transducer and method," US Patent #4,358,678 (November 9, 1982).

J. N. Liu et al., "Development of a porous polymer pH optrode," *Opt. Lett.* **17**(24), 1815 (1992).

J. M. López-Higuera, ed., *Handbook of Optical Fibre Sensing Technology*, John Wiley & Sons, New York (2002).

J. M. López-Higuera, J. Jones, M. Lopez-Amo, and J. L. Santos, eds., *Int. Conf. Opt. Fibre Sensors*, Proceedings of SPIE (1998–2014).

A. Mendez and T. F. Morse, *Specialty Optical Fibers Handbook*, Academic Press, Amsterdam (2007).

J. H. Porter, "Differential Fiber Optic Differential Pressure Sensor," US Patent #4,210,029 (July 1, 1980).

B. E. A. Saleh and M. C. Teich, *Fundamentals of Photonics*, John Wiley & Sons, New York (1991).

Bibliography

- G. B. Scott and D. E. Lacklison, "Magneto-optic Properties and Applications of Bismuth Substituted Iron Garnets," *IEEE Trans. Magnetics* **12**(4), 292 (1976).
- W. B. Spillman, Jr., "Multimode fiber-optic hydrophone based on a Schlieren technique," *Appl. Opt.* **20**(3), 465 (1981).
- W. B. Spillman, Jr., "The evolution of smart structures/materials," Proc. 1st European Conf. Smart Structures and Materials, p. 97, CRC Press (1992).
- W. B. Spillman, Jr. and D. H. McMahon, "Frustrated-total-internal-reflection multimode fiber-optic hydrophone," *Appl. Opt.* **19**(1), 113–117 (1980).
- W. B. Spillman, Jr. and D. H. McMahon, "Multimode fiber optic hydrophone based on the photoelastic effect," *Appl. Opt.* **21**(19), 3511 (1982).
- W. B. Spillman, Jr. and D. H. McMahon, "Multimode fiber optic sensors based on the photoelastic effect," *Proc. SPIE* **412**, 110–114 (1983) [doi: 10.1117/12.935803].
- W. B. Spillman, Jr. and R. E. Rudd, "Enhanced performance Faraday sensor," *Proc. SPIE* **2070**, 294–304 (1993) [doi: 10.1117/12.169910].
- W. B. Spillman, Jr., D. R. Patriquin, and D. H. Crowne, "Fiber optic linear displacement sensor based upon a variable period diffraction grating," *Appl. Opt.* **28**(17), 3550 (1989).
- W. B. Spillman, Jr. et al., "A 'smart' bed for non-intrusive monitoring of patient physiological factors," *J. Meas. Sci. Technol.* **15**(8), 1614 (2004).
- W. B. Spillman, Jr. et al., "Statistical mode sensor for fiber optic vibration sensing applications," *Appl. Opt.* **28**(15), 3166 (1989).
- P. S. Theocaris and E. E. Gdoutos, *Matrix Theory of Photoelasticity*, Springer-Verlag, Berlin (1979).
- E. Udd, "An overview of fiber optic sensors," *Rev. Sci. Instruments* **66**(8), 4015 (1995).

Bibliography

- E. Udd, "Fiber optic smart structures," *Proc. IEEE* **84**(6), 884–894 (1996).
- E. Udd, ed., *Fiber Optic Smart Structures*, John Wiley & Sons, New York (1995).
- E. Udd and W. B. Spillman, Jr., *Fiber Optic Sensors: an Introduction for Engineers and Scientists*, 2nd Ed., John Wiley & Sons, Hoboken, NJ (2011).
- C. A. Villarruel et al., "Evanescent wave fiber optic chemical sensor," *Proc. SPIE* **798**, 225–229 (1987) [doi: 10.1117/12.941110].
- J. D. Weiss, "Fiber Optic Sensor Employing Successively Destroyed Coupled Points or Reflectors for Detecting Shock Wave Speed and Damage Location," US Patent #5,446,278 (August 29, 1995).
- A. Yariv, *Introduction to Optical Electronics*, 2nd Ed., Holt, Rinehart and Winston, New York (1976).
- S. Yin, P. B. Ruffin, and F. T. S Yu, *Fiber Optic Sensors*, 2nd Ed., CRC Press, Boca Raton, FL (2008).

Index

- acoustic detection, 39
- aircraft actuator position, 45
- angular position, 37
- anti-Stokes, 80
- avalanche photodiode, 13
- axial displacement, 34

- backscatter signal, 54
- bandgap, 10
- beat signals, 91
- birefringence, 17
- bismuth-substituted iron garnet, 46
- blackbody, 52
- blackbody cavity, 53
- blackbody radiation, 7
- blast wave, 55
- Bragg condition, 20
- Bragg grating, 67, 68
- breaking, 101
- breathing rate, 90

- calibration curves, 6
- chirped grating, 44, 45
- chopper, 21
- circular polarization, 18
- civil structure applications, 87
- closed-loop approach, 63
- closed-loop fiber optic gyro, 64
- closure sensors, 93
- coherence multiplexing, 78
- component selection, 23
- composite materials, 95
- conduction band, 10
- configuration trade-offs, 23
- Congo Red pH indicator, 49
- connectors, 15
- cost, 23
- coupling loss, 34
- coupling modulation, 35

- dark-current noise, 5
- decay time, 51
- deformer spacing, 28
- depletion region, 11–12
- design protocol, 24
- difference/sum detection, 39
- diffraction, 40
- diffraction grating, 19, 41
- diffraction order, 40
- direct modulation, 21
- distributed Brillouin sensor, 81, 82
- distributed feedback lasers, 11
- distributed Raman sensor, 80
- distributed Sagnac sensor, 83
- distributed Sagnac–Mach–Zehnder sensor, 84
- dither, 59
- double heterostructure laser, 11

- electro-optic effect, 7
- electromagnetic wave, 3
- elliptical polarization, 18
- endoscope, 2
- evanescent field, 56
- evanescent-wave chemical sensor, 57
- excited electrons, 50

Index

- Fabry–Pérot etalon, 72
- Faraday mirrors, 62
- fast axis, 17
- fiber Bragg grating (FBG), 19–20
- fiber depolarizer, 100
- fiber etalon sensors, 73
- fiber light sources, 98
- fiber optic sensor, 1
 - advantages, 2
 - intrinsic, 1
 - extrinsic, 1
- figure-eight configuration, 31
- final sensor development, 24
- finesse, 72
- fluid-level sensor, 27
- fluorescence, 50–51
- fluorescence decay, 7
- Fourier transform, 91
- free spectral range, 72
- frequency division
 - multiplexing (FDM), 77
- Fresnel equations, 30
- frustrated total internal reflection (FTIR), 25

- gain, 13
- gas-turbine engine speed, 47
- genetic algorithm, 23
- Georges Sagnac, 63
- graded index, 9
- grating equation, 40–41
- GRIN lenses, 16

- heart rate, 90
- high-temperature optical fiber, 53
- hydrophone, 26

- instantaneous
 - polarization, 18
- integrated optics, 97
- intensity modulation, 21
- intracranial pressure sensor, 35
- intrinsic, 73
- intrinsic region, 12

- lenses, 16
- lensmaker's formula, 16
- light modulation, 4
- light-emitting diode (LED), 10
- linear polarization, 18
- linear polarizers, 36
- linear position sensors, 44
- lithium niobate, 97
- lock-in amplifier, 103
- longitudinal displacement, 34

- Mach–Zehnder
 - Hydrophone, 60
 - interferometer, 58–59, 61
- macrobending, 30–31
- magnetic moments, 46
- magneto-optic effect, 7
- magneto-optic material, 46
- manual selection, 23
- Maxwell's equations, 3
- methylene blue dye, 57

Index

- Michelson interferometer, 62
- microbending, 28–29
- modal domain, 32–33
- modes, 8
- modulators, 21
- monochromatic signal, 14
- multimode optical fibers, 1

- n-type semiconductor, 10
- National Institutes of Health (NIH), 48
- neutron detection, 92
- numerical aperture (NA), 34

- oil and gas pipelines, 94
- open-loop fiber optic gyro, 64
- opposed-grating structure, 43
- optical absorption, 7
- optical fiber connectors, 15
- optical fibers, 1, 8–9
- optical frequency domain reflectometry (OFDR), 76
- optical retarder, 38
- optical time domain reflectometry (OTDR), 54–55
- optical transducer, 22
- optimization techniques, 23
- optrode, 48

- p-i-n junction, 12
- p-n junction, 12
- p-polarized, 30
- p-type semiconductor, 10
- performance, 23
- periodic stress, 28
- pH, 49
- phase difference, 17
- phase modulation, 21
- phase noise, 77
- phase-sensitive detection, 103
- photochromic, 33
- photoconductive mode, 5, 12
- photodiode optical detector, 12
- photoelastic effect, 38
- photomultiplier tube (PMT), 13
- photovoltaic mode, 12
- plane of incidence, 30
- plane wave, 3
- Planck's radiation law, 52
- plastic optical fibers, 96
- polarization, 17, 36
- polarization-preserving optical fibers, 99–100
- polarizers, 18
- position sensors, 89
- possible polarizations, 36
- pressure sensing, 39
- pressure sensor, 29, 31, 71
- properties of light, 4
- proximity sensor, 2, 93

- quadrature detection, 59
- quantum well lasers, 11
- quenched, 50

- radiation dosage, 92
- reflection coefficients, 30

Index

- responsivity, 12
- RGB sensors, 14
- robotic surgery, 91

- s-polarized, 30
- Sagnac acoustic sensor, 65
- Sagnac effect, 7
- Sagnac interferometer, 58, 85
- Sagnac rotation sensor/
 fiber optic gyro, 64
- Sagnac strain sensor, 66
- Schlieren sensors, 42
- scribing, 101
- secure-communication
 mode, 85
- semiconductor laser diode,
 11
- semispherical lenses, 102
- sensor specification, 22
- shaft rotation, 41
- shot noise, 5
- signal-to-noise ratio
 (SNR), 5
- single-mode
 interferometers, 58
- single-mode optical
 fibers, 1
- slipknot configuration, 31
- slow axis, 17
- smart bed, 90
- Snell's law, 16, 25, 30
- spatial multiplexing, 79
- speckle, 32
- splices, 15, 102
- spreadsheet analysis, 23
- step-index fiber, 8, 9
- Stokes, 80
- strain imaging, 95
- strain sensors, 86
- strain-optic effect, 7
- swept frequency laser, 91

- tapered fiber, 56
- thermal (Johnson) noise,
 5
- through-transmission
 optrode, 49
- time division multiplexing
 (TDM), 74–75
- total internal reflection
 (TIR), 8, 25
- trade-off study, 22
- transduction, 6
- transverse strain, 70

- ultraviolet (UV) epoxy,
 102
- v-groove, 15


- V-number, 8
- valence band, 10
- velocity of detonation
 (VOD), 55
- vertical-cavity surface-
 emitting lasers, 11
- virtual apertures, 33

- wavelength division
 multiplexing (WDM),
 75
- wavelength modulation,
 21
- waveplate, 17
- Wein's law, 52
- windowing, 91



William B. Spillman, Jr., is a retired Associate Professor of Physics at Virginia Tech. He received his A.B. in Math-Physics from Brown University in 1968 and his M.S. and Ph.D. in Physics from Northeastern University in 1972 and 1977, respectively. Prior to his academic career, he worked as a scientist, research

manager, and director of research for Sperry Corp., Geo-Centers, Inc., Hercules, Inc., and the Goodrich Corp., among others. He is the co-author/editor of 7 books and more than 180 technical publications. He also holds 46 US patents. In 1997, he was elected a Fellow of SPIE, and in 2000 he received a SPIE recognition award for his society activities in smart structures and materials. He was elected a Fellow and Chartered Physicist in 2001 and a Chartered Scientist in 2004 by the Institute of Physics in the UK. In February 2006, he received a Lifetime Achievement Award from SPIE for his research and professional activities in smart materials and structures. He has been active in the field of fiber optic sensing since its inception, with numerous publications and patents.



Eric Udd is President of Columbia Gorge Research, a company he founded to promote fiber optic sensor technology and its applications. He has been involved in the field of fiber optic sensors since 1977, with fundamental contributions to fiber rotation, acceleration, acoustic, pressure, vibration, strain, tem-

perature, humidity and corrosion sensors. At McDonnell Douglas (1977–1993), he managed over 30 government and commercial programs on fiber optic sensors that resulted in products used on the 777 and other commercial aircraft, launch vehicles, and spacecraft. In 1993, Udd founded Blue Road Research, working on civil structures, oil and gas projects, aerospace, and defense. In January 2006, he began full-time work at Columbia Gorge Research and developed new applications in the electric power and medical fields, as well as aerospace and defense.

Udd has 48 issued US Patents, with additional applications pending. He has written over 150 papers, chaired more than 30 international conferences on fiber sensors, edited textbooks, and contributed many book chapters. He is a McDonnell Douglas Fellow, an SPIE Fellow, and an OSA Fellow. He was awarded the David Richardson Medal by OSA in 2009 for his work on fiber optic sensors and the field of fiber optic smart structures.