

Index

A

- accelerometer, 26
- acoustic sensor, 27, 266, 268
- acousto-optic modulator, 24, 30, 266
- aether, 2
- aircraft, 29
- Allan deviation, 14
- Allan variance, 171
- amplified spontaneous emission (ASE), 8
- amplified spontaneous emission, 149
- angle error, 109
- angle random walk (ARW), 48
- attitude referencing, 99

B

- backscatter, 30
- backscattering noise, 161
- beamsplitter, 31
- bias error, 155
- bias instability, 49
- bias offset error, 48
- bias stability, 115
- biasing modulation amplitude, 162
- biasing modulation–demodulation, 6
- biasing modulation, 158
- birefringence modulation, 159
- Brillouin gain spectrum, 118
- Brillouin optical time-domain analyzer (BOTDA), 11
- broadband spontaneous-emission source, 8

C

- capillary waves, 153
- carrier suppression, 169, 172
- closed loop, 21, 266
- closed-loop scheme, 6
- coherence collapse, 161
- coherence function, 9
- coherent backscattering noise, 152, 163
- coherent backscattering, 155
- common input–output port, 5

D

- D-shaped cross-section, 43
- deadbeat control filter, 102
- depolarization length, 159
- detector noise, 162
- digital phase ramp, 6
- dispersion, 24
- distributed polarization extinction ratio (PER), 9
- distributed scattering, 155
- distributed strain, 118
- DSP-1750, 53
- DSP-1760, 55
- DSP-3000, 53
- dynamic biasing modulation, 173

E

- E•Core fiber, 43
- E•Core fiber:1000 and 50, 2000
- eigenfrequency, 102
- elliptical core, 39

erbium-doped fiber amplifier

(EDFA), 8

extinction ratio, 157

F

Faraday effect, 12, 152

fiber crossover, 221

fiber optic gyro (FOG), 1

fiber optic gyroscope (FOG), 39, 42

fiber optic gyroscope (FOG):

open-loop, 46

fiber trimming, 253

filters, 27

Fizeau's experiment, 3

four-state modulation, 6

Fresnel–Fizeau drag effect, 3

G

Gaussian distribution, 156

Gaussian white noise (GWN),

154, 167

glass bobbin, 117

group birefringence, 224

guidance system, 261

H

hardware-in-the-loop (HITL), 102

HITL, 106, 108

hollow-core fiber (HCF), 153, 174

hollow-core micro-structured

fiber, 12

I

IMU:1725, 57

IMU:1750, 56

IMU:1775, 56

inertial measurement unit (IMU), 42

inertial navigation system (INS), 42

inertial navigation system:

GEO-FOG 3D, 58

inertial reference unit (IRU), 99

inertial systems, 39

insertion loss (IL), 219

integrated-optic channel

waveguide, 14

K

Kerr constant, 175

Kerr effect, 152

Kerr phase error, 160

knife-edge near-field Fresnel diffraction, 17

L

launch vehicles, 35

level-wound coil, 46

license, 26

linewidth broadening, 161, 164

Lloyd mirror effect, 16

lock-in, 30

M

Mach–Zehnder, 268

magnetic dependence, 13

magneto-optic modulator, 31

McDonnell Douglas Astronautics Company (MDAC), 261

McDonnell Douglas, 266

mechanical gyros, 29, 261

Michelson interferometer, 268

minimum configuration, 31

Monte Carlo simulation, 104

multi-integrated optical circuit (MIOC), 102

multifunction integrated optic circuit (MIOC), 154

multiple function integrated optical chip (MIOC), 218

N

navigation accuracy, 99

navigation and control, 60

navigation-error equations, 103

noise spectrum, 156

noise, 266, 268

O

- octapole winding, 115
- oil and gas industry, 26
- open-loop fiber optic gyro, 33
- optical circuit, 44
- optical coherence domain
 - polarimetry (OCDP), 9
- optical coherence tomography (OCT), 216, 254
- optical coherence-domain polarimeter (OCDP), 222
- optical fiber, 42
- optical Kerr effect, 8
- optical spectrum analyzer (OSA), 9

P

- path-matched interferometry, 9
- phase error, 158
- phase noise, 155
- phase nulling, 24, 266
- photon noise, 14
- photonic crystal, 153
- piezoelectric (PZT) modulator, 47
- piezoelectric modulator, 31
- pointing error, 251
- polarization control, 268
- polarization coupling, 157–158
- polarization extinction ratio (PER), 219
- polarization rejection, 16
- polarization-maintaining (PM) fiber, 155
- polarizer, 31, 157
- positioning and imaging, 60
- proper frequency, 6
- proton-exchanged lithium niobate (LiNbO_3) integrated-optic circuit, 9
- pseudo-random bit sequence (PRBS), 153, 166

Q

- quadrupolar winding, 11
- quadrupole winding method, 46
- quadrupole winding, 115

R

- random bit sequence (RBS), 166
- rate error, 109
- reciprocal configuration, 4
- relative intensity noise (RIN), 10, 13, 149, 162
- relative intensity noise (RIN): reduction, 14
- remotely operated vehicles (ROVs), 58
- ring laser gyro (RLG), 29, 32, 149
- rocket, 264
- rotation sensitivity, 162
- rovers, 34

S

- Sagnac distributed sensor, 28–29
- Sagnac interferometer, 47, 218
- Sagnac secure fiber optic communication, 29, 273
- Sagnac strain sensor, 27
- Sagnac–Laue effect, 2
- Sagnac’s experiment, 2
- sawtooth, 31
- scale factor, 6, 31, 99, 149
- self-heterodyne method, 161
- shock and vibration sensitivity, 49
- Shupe constant, 175
- Shupe effect, 11, 115, 152, 172, 218
- Shupe error, 119
- Shupe sensitivity, 115
- sinusoidal phase modulation, 164
- spacecraft, 29
- spatial resolution, 118
- special theory of relativity, 2
- stabilization and orientation, 61

static parameters, 220
strain attenuation, 117
strain distribution, 117
super-luminescent diode
(SLD), 14
super-luminescent diode source
(SLED), 224
superfluorescent fiber source
(SFS), 149
symmetric coil, 120
symmetrical winding, 115

T
temperature sensitivity, 49
thermal drift, 177
thermal strain, 117
ThinFiber, 39

total internal reflection (TIR), 15
transient parameters, 220

U

unpolarized emission, 9
US Air Force (USAF), 267

V

Verdet constant, 176

W

white noise, 168
winding defects, 219
winding, 116

Y

Y-junction, 154