

Index

- 3rd-order astigmatism, 22, 89
 - 3rd-order spherical, 22, 89
 - 3rd-order trefoil, 22, 89
 - 3rd-order x coma, 22, 89
 - 3rd-order y coma, 22, 89
 - 45° trefoil, 22, 89
 - 5th-order astigmatism, 22, 89

 - ABC parameters, See Dill parameters
 - aberrations, lens, 20–23, 92
 - absorption coefficient, 41, 42, 44, 92
 - acid-catalyzed resist, 40, 92
 - across-chip linewidth variation (ACLV), 64
 - actinic wavelength, 92
 - activation energy, 46, 92
 - additive processes, 10
 - adhesion promoter, 3, 92
 - advanced process control (APC), 92, 93
 - aerial image, 13, 17, 23, 49, 53, 92
 - aligner, See mask aligner
 - alignment, 93
 - alignment key, 93
 - alignment mark, 93
 - alignment target, 93
 - alternating phase-shift masks, 78, 79, 93
 - annular illumination, 84, 93
 - antireflective coating (ARC), 37, 38, 93
 - aperture stop, 93
 - aperture, numerical, See numerical aperture
 - ArF, 93
 - Arrhenius coefficient, 46, 93
 - Arrhenius equation, 46, 93
 - aspect ratio, 94
 - astigmatism, 22, 24, 94
 - atomic force microscope (AFM), 67

 - attenuated phase-shift masks, 78, 80, 94
 - autofocus system, 94

 - bandwidth, illumination, 23, 94
 - base quencher, 47
 - Beer's law, 41, 42, 90
 - bias, 81, 94
 - binary mask, 94
 - birefringence, 94
 - bleaching, photoresist, 42, 44, 94
 - Bossung curves, 69, 94
 - bottom antireflection coating (BARC), 38, 94

 - CAR, 40, 94
 - catadioptric, 94
 - catalyze, 7, 40, 45
 - catoptric, 94
 - Cauchy coefficients, 95
 - characteristic curve, See contrast curve
 - chemically amplified resists, 7, 40, 45, 46, 57, 95
 - chromatic aberration, 23, 95
 - chrome on glass, 80
 - circular polarization, 29
 - clearing dose (E_0), See dose to clear
 - coating, resist spin, 4, 95
 - coherence factor, 19, 95
 - coherence, spatial, 18, 19, 95
 - coherent illumination, 18, 19, 95
 - coma, 22, 95
 - condenser lens, 13, 95
 - contact printing, 6, 95
 - contrast curve, 95
 - contrast enhancement layer (CEL), 96
 - contrast, image, 95
 - contrast, resist, 59, 95
 - corner rounding, 96
-

Index (cont'd)

- critical dimension (CD),
 - 61–63, 94, 96
 - critical dimension variational equation, 63, 91
 - critical shape (CS), 96
 - critical shape difference (CSD), 96
 - critical shape error (CSE), 96
 - deblocking, 40, 45
 - deep-UV lithography, 96, 98
 - defocus, 25, 54, 69, 96
 - degree of coherence, 19, 96
 - dehydration bake, 3, 96
 - depth of focus (DOF), 31, 32,
 - 70–73, 83, 97
 - descum etch, 9
 - design rule, 97
 - developer, 8, 51, 97
 - development, 8, 49–51, 59, 97
 - development path, 52
 - development rate, 49–51, 97
 - development rate monitor (DRM), 97
 - diffraction, 14, 15, 97
 - diffraction orders, 15, 32, 73,
 - 97
 - diffraction-limited, 17, 97
 - diffraction pattern, 15, 97
 - diffusion, 7, 46, 90
 - diffusion coefficient, 46, 98
 - diffusion equation, 46, 90
 - diffusion length, 57, 98
 - diffusivity, *See* diffusion coefficient
 - Dill parameters, 42–44, 90,
 - 92, 97
 - dioptric, 98
 - dipole illumination, 83, 98
 - direct-write lithography, 87, 98
 - dispersion, 23, 98
 - dissolution inhibitor, 98
 - dissolution promoter, 98
 - dissolution rate, 48, 49, 51,
 - 59, 90, 98
 - distortion, 98
 - dose, 43, 69, 98
 - dose to clear (E_0), 26, 36, 98
 - dose to size, 99
 - DRM, 99
 - dyed resist, 99
 - e-beam lithography, *See* electron beam lithography
 - edge bead, 99
 - edge bead removal (EBR), 99
 - electric field image at the wafer, 17, 88
 - electromagnetic wave, 11, 27,
 - 29
 - electron beam lithography,
 - 87, 98, 99
 - elliptical polarization, 29
 - embedded PSM (EPSM), 80, 99
 - entrance pupil, lens, 99
 - etching, 9
 - excimer laser, 99
 - exit pupil, lens, 21, 29, 75, 99
 - exposure, 6, 43, 99
 - exposure dose, *See* exposure energy
 - exposure energy, 43, 69, 100
 - exposure field, *See* field, exposure
 - exposure latitude, 62, 71, 100
 - exposure margin, 100
 - extinction coefficient, 100
 - extreme ultraviolet (EUV) lithography, 87, 99, 100
 - fab, 100
 - FE matrix, 69, 71, 101
 - field-by-field alignment, 100
 - field curvature, 100
 - field, exposure, 100
 - first law of photochemistry, 43
 - first-order kinetics, 43, 45
 - flare, 26, 100
 - flare measurement, 26, 89
-

Index (cont'd)

- flood exposure, 100
 - focal plane, 100
 - focal position, *See* focus
 - focus, 69, 101
 - focus-exposure matrix, 69, 71, 101
 - focus-exposure process
 - window, 69, 71
 - forbidden pitch, 84
 - Fourier optics, 17, 101
 - Fourier transform, 15, 17
 - Fourier transform of 1D mask pattern, 15, 88
 - Fraunhofer diffraction, 14, 15
 - Fresnel, Joseph, 14
 - Fresnel reflection formulae, 35, 90

 - g-line, 101
 - GDS II, 101
 - glass transition temperature, 101
 - global alignment, 101

 - H-D Curve, 101
 - h-line, 101
 - H-V bias, 24, 101
 - hard bake, 9, 102
 - hexamethyldisilazane (HMDS), 3
 - horizontal-vertical bias, 24, 89, 101
 - Hurter-Driffeld curve, *See* H-D curve
 - Huygen's principle, 14, 102

 - i-line, 102
 - IC, *See* integrated circuit
 - illumination system, 13, 102
 - illumination, Köhler, 102
 - image contrast, 102
 - image log-slope (ILS), 53, 56, 102
 - image reversal, 102
 - immersion lithography, 31, 32, 37, 87, 91, 102
 - immersion-high NA depth of focus Rayleigh criterion, 32, 91
 - imprint lithography, 87, 102
 - incoherent illumination, 19, 102
 - index of refraction, 30, 31, 34, 37, 38, 78, 111
 - integrated circuit, 1, 103
 - intensity, 27, 34, 103
 - internal transmittance, 34, 90
 - invariant, optical 30, 31, 89
 - inverse Fourier transform, 17
 - ion beam lithography, 103
 - ion implantation, 10
 - iso-dense print bias, 81, 103
 - isofocal bias, 103
 - isofocal dose, 103
 - isofocal linewidth, 103

 - Köhler illumination, 103
 - Kirchhoff diffraction, 14
 - KrF, 103

 - Lagrange invariant, 30
 - Lambert law of absorption, 41, 90
 - latent image, 40, 43, 45, 56, 57, 103
 - latent image gradient, 56, 57
 - Levenson PSM, *See* alternating PSM
 - lift-off process, 104
 - lifting, resist, 103
 - line edge roughness (LER), 66, 104
 - line end shortening (LES), 103, 104
 - linescan, 67
 - linewidth, 61, 67, 104
 - linewidth roughness, 66
 - lithographic cluster, 2
 - lithographic imaging equation, 59
-

Index (cont'd)

- lithography, 1, 104
 - log-slope defocus curve, 55
 - LSI, 104

 - Mack 4-parameter dissolution rate model, 49, 90
 - magnification factor, 16
 - mask, 13, 76, 78–80, 104
 - mask aligner, 104
 - mask biasing, 82, 104
 - mask blank, 105
 - mask error enhancement factor (MEEF), 76, 91, 105
 - mask error factor, *See* mask error enhancement factor
 - mask linearity, 105
 - maskless lithography, 105
 - Maxwell's equations, 11, 27, 88
 - MEF, *See* mask error enhancement factor
 - mercury arc lamp, 105
 - metrology, 67, 68, 105
 - microlithography, 1, 105
 - mix-and-match lithography, 105
 - modeling, 85, 105
 - Moore's law, 86, 105
 - multilayer resist (MLR), 106

 - nanolithography, 106
 - negative photoresist, 106
 - next-generation lithography (NGL), 87, 106
 - non-bleachable absorption coefficients, 42, 44
 - normality, developer, 51
 - normalized image log-slope (NILS), 53–60, 66, 91, 106
 - Novolak/DNQ, 39
 - numerical aperture (NA), 16, 17, 55, 106

 - OAI, 77, 83, 106
 - objective lens, 13, 106

 - off-axis illumination (OAI), 77, 83, 106
 - OPC, 77, 80, 82, 106
 - optical density, 106
 - optical invariant, 30, 31, 89
 - optical lithography, 1, 2, 106
 - optical path difference (OPD), 25, 75, 89, 107
 - optical path difference due to defocus, 89
 - optical proximity correction (OPC), 77, 80, 82, 107
 - optical proximity effect, 81, 107
 - overlay, 65, 68, 107
 - overlay correctables, 68, 107
 - overlay mark, 68, 107
 - overlay mark fidelity, 107

 - paraxial approximation, 107
 - partial coherence, 19, 107
 - partial coherence factor, 19
 - partially coherent illumination, 19, 108
 - pattern placement error, 108
 - patterning, 1, 9, 108
 - pellicle, 108
 - phase conflict, 79
 - phase-shift mask (PSM), 77–80, 108, 109
 - phasor, 12, 88
 - photoacid generator (PAG), 45, 107, 108
 - photoactive compound (PAC), 39, 43, 107, 108
 - photolithography, 1, 2, 108
 - photomask, 6, 78, 108
 - photoresist, 1, 2, 108
 - photoresist contrast, 59, 108
 - photoresist dissolution, 49–52, 59
 - piston, 22
 - pitch, 15, 73, 81, 83, 109
 - plane wave, 12, 34, 88
 - point spread function, 73, 108
-

Index (cont'd)

- polarization, 27, 29, 109
 - positive photoresists, 39, 109
 - post-apply bake (PAB), 5, 48, 107, 109
 - post-exposure bake (PEB), 7, 45, 46, 57, 108, 109
 - post-exposure delay, 47
 - postbake, 9, 109
 - power (focus), 22, 88
 - prebake, 5, 48, 109
 - process control, 63
 - process error, 62
 - process latitude, 62, 109
 - process optimization, 63
 - process window, 70, 109
 - projection e-beam, 87
 - projection printing, 6, 109
 - proximity baking, 5, 109
 - proximity effects, 81, 110
 - proximity printing, 6, 110
 - puddle development, 8
 - pupil filter, 110
 - pupil function, 17, 88, 110
 - pupil phase error due to defocus, 89
 - pupil, lens, 17, 110

 - quadrupole illumination, 83, 110
 - quantum efficiency, 110

 - random polarization, 29
 - raster scan, 110
 - Rayleigh depth of focus criterion, 32, 75, 91
 - Rayleigh equations, 74, 75, 91, 110
 - Rayleigh resolution criterion, 74, 91
 - reactive ion etching, 10
 - reciprocity, 43
 - reflection coefficient, 34, 35, 90
 - reflective notching, 111
 - reflectivity, 34, 35, 111

 - refractive index, See index of refraction
 - registration, 111
 - resin, photoresist, 111
 - resist, 1, 2, 111
 - resist contrast (gamma), 51, 59, 111
 - resist linewidth, 61, 111
 - resist reflectivity, 36, 111
 - resist stripping, 9, 114
 - resolution, 31, 73, 74, 77, 111
 - resolution enhancement technologies (RET), 77, 111
 - reticle, 111

 - sagittal lines, 112
 - scalar wave theory, 112
 - scanners, 6, 112
 - scanning electron microscope (SEM), 67, 112
 - scattering bars, 82, 112
 - semiconductor device, 112
 - sensitizer, 39, 112
 - sensitizer decomposition, 48
 - serifs, 82, 112
 - sidelobes, 80
 - sidewall angle, 61, 69, 112
 - simulation, 85, 112
 - smiley plot, 69, 100, 112
 - Snell's law, 30
 - soft x-ray lithography, 112
 - softbake, 5, 48, 112
 - solvent, photoresist, 42, 113
 - spatial coherence, 18
 - spatial frequencies, 74, 113
 - spherical aberration, 22, 89, 113
 - spider plot, 69, 113
 - spin coating, 4, 113
 - spin development, 8
 - spin speed curve, 4
 - spray development, 8
 - standing waves, 7, 33, 34, 38, 113
-

Index (cont'd)

- step-and-repeat camera, 6, 113
 - step-and-scan, 6, 113
 - steppers, 6, 113
 - Strehl ratio, 113
 - sub-resolution assist feature (SRAF), 82, 114
 - substrate, 114
 - substrate cleaning, 3
 - substrate reflectivity, 114
 - surface induction, 50, 114
 - surface inhibition, 50, 114
 - surfactants, 50, 114
 - swing curve, 36–38, 114
 - swing ratio, 114

 - T-top, resist profile, 47, 114
 - tangential lines, 115
 - thermal dose, 45
 - tool-induced shift (TIS), 68, 115
 - top antireflection coating, 37, 115
 - top surface imaging, 115
 - transmission coefficient, 34, 90

 - ULSI, 115
 - unpolarized, 29
 - UV, 115
 - UV cure, 115

 - vapor prime, 3, 115
 - vector scan, 115
 - vector wave theory, 27, 115
 - VLSI, 116

 - wafer, 13, 116
 - wafer-induced shift, 68
 - wafer fab, 116
 - wavefront, 12, 14, 20, 116

 - X tilt, 22, 88
 - x-ray lithography, 116

 - Y tilt, 22, 88

 - Zernike coefficients, 21, 22, 88, 116
 - Zernike formulae for aberrations, 22, 88
 - Zernike polynomial, 21, 22, 88, 116
-



Chris A. Mack received Bachelor of Science degrees in physics, chemistry, electrical engineering, and chemical engineering from Rose-Hulman Institute of Technology in 1982, a Master of Science degree in electrical engineering from the University of Maryland in 1989, and a Ph.D. in chemical engineering from the University of Texas at Austin in 1998.

Dr. Mack founded FINLE Technologies, the developer of the lithography simulation software PROLITH, in 1990, serving as President and Chief Technical Officer until the acquisition of FINLE by KLA-Tencor in 2000. For the next five years he served as Vice President of Lithography Technology for KLA-Tencor. In 2003 he received the SEMI Award for North America for his efforts in lithography simulation and education. He is also an adjunct faculty member at the University of Texas at Austin. Currently, he writes, teaches, and consults on the field of semiconductor microlithography in Austin, Texas, where he lives with his wife Susan and their daughter Sarah.