

Index

- 126-nm light, 433
- 157-nm light, 433, 438
- 157-nm lithography, 205

- A**
- Abbe error, 212, 213
- aberrations, 129, 130, 133, 135, 136, 138, 164, 183, 428
 - chromatic, 136–138
 - coma, 133, 134, 275
 - spherical, 133, 134
- absorber material, 292
- acceleration, 214
- accuracy, 397
- across-field linewidth variations, 130
- actinic, 8
- address, 300
- adhesion promotion, 1, 57
- adhesive, 202
- advanced mechanical modeling
 - technique, 460
- AEBLE 150, 532
- Aerial Image Measurement System (AIMS), 136, 164, 327
- air bearings, 213
- Airy pattern, 13
- alignment, 2, 243
 - mark, 244, 245
 - system, 244
 - target, 244
- ALTA
 - 4700, 310
 - system, 310
- alternating phase-shifting mask, 370, 373, 378, 467
- aluminum oxide, 432
- annular illumination, 350, 351

- antireflection coating (ARC), 150–154, 157, 167, 197
 - top, 153, 154
- APEX-E, 77
- Applied Materials, 310
- Ar₂* wavelength, 433
- ArF optical lithographic technology, 398
- ARPA-NIST standard, 524
- ASM Lithography, 171, 173, 218, 223
- aspect ratios, 82
- aspheric surface, 202
- aspherical lens elements, 206
- astigmatism, 40, 41, 43, 135
- asymmetric magnification, 260
- asymmetries in overlay targets, 277
- atomic force microscope, 397
- attenuated phase-shifting mask, 375, 379
- autofocus system, 171, 207
- axicon, 188
- azimuthal angle, 501

- B**
- backscattered electron, 391
- backscattering, 302, 303
- bananicity, 133
- bandwidth, 194
- BARLi, 153
- barometric pressure, 47, 203
- baseline error, 248, 251
- beam-angular divergence, 533
- beam-delivery systems, 179
- beam energy, 302
- bearings, 213
 - air, 213
- beryllium window, 527

- bilayer resist process, 104
- birefringence, 194, 203, 291
- blazed diffraction grating, 353
- bleaching, 140
- borosilicate glass, 290
- Bossung curve, 44
- Bragg condition, 476
- bright field, 247
- bubble, 425
- bubble lifetime, 425
- butting error, 298
- C**
- calcium fluoride (CaF₂), 193, 194, 202, 205, 432
- Canon, 171, 173, 191, 223, 252
 - quadrupole effect for stepper technology (CQuest), 350
- capacitance gauges for focusing, 208
- capital
 - cost, 457
 - depreciation, 458
- carbon deposition, 397
- Carl Zeiss, 171, 191
- catadioptric lens, 181, 199, 201, 499
- cell-projection
 - e-beam lithography, 538
- centration, 202
- characteristic curve, 24, 29
- chemical amplification, 75, 77, 85, 502
- chemical epitaxy, 547
- chemical-mechanical polishing, 277, 278, 409, 427, 436
- chill plate, 70
- chromeless
 - mask lithography, 374
 - phase-shifting lithography, 374, 375, 378, 467
- chromium, 292
 - wet etchant, 316
- chuck nonflatness, 43
- clocked, 203
- CO₂ laser, 494
- coherent
 - illumination, 17
 - light, 11
- collection optics, 496
- compaction, 195
- conjugate, 44
- consumables costs, 179, 466
- contact
 - angle, 58, 59
 - holes, 55
 - printing, 169, 219
- contamination, 485
- contrast, 24, 53, 86–88, 105, 116
 - enhancement, 105
- convection ovens, 69
- Corning, 497
- cosine error, 214, 266
- cost-of-ownership, 455, 458
- Cymer, 184, 495
- D**
- dark field, 247
 - alignment, 252
- data
 - format, 296
 - compression, 530
- decompaction, 195
- defect, 423
- dense optical proximity correction, 364
- depth-of-field, 291
- depth-of-focus, 33–36, 38, 39, 43, 44, 190, 421, 426
 - individual, 40, 42
 - usable, 40, 42
- design cost, 468
- design for manufacturability, 382, 439
- developer normality, 81
- development, 2
 - rates, 159
- diazonaphthaquinone (DNQ), 72–75, 77
- die-by-die alignment, 253, 459
- diffracted beams, 12

- diffraction, 10, 13, 19, 125, 163
 - grating, 10
 - limit, 136, 427
 - limited, 129
 - diffractive optical element (DOE), 188, 353
 - diffusion-enhanced silylating resist (DESIRE), 104, 122
 - diffusion, 148, 435
 - coefficients, 149
 - Dill parameters, 140
 - direct-write electron-beam lithography, 532
 - directed self-assembly, 544
 - discharge-produced plasma, 494
 - source, 492
 - dispersion, 192
 - distortion, 135, 183
 - 3rd order, 268
 - 5th order, 268
 - Doppler shift, 210
 - dose control, 186, 187
 - dose to clear, 24
 - double Gaussian, 190
 - double-patterning, 441, 443, 447
 - downtime, 463
 - DSW4800, 171, 173
 - dual-stage exposure tool, 218
 - dyed resists, 150, 157
 - dynamic dispense, 63
- E**
- E-zero, 24
 - EBM-7000, 297
 - edge bead, 68, 72
 - edge-placement error, 364
 - electric-field-induced metal migration, 323
 - electrical linewidth metrology, 405, 407
 - electron beam
 - assisted chemical etching, 325
 - direct-write lithography, 530
 - exposure system, 293
 - lithography, 529
 - writer, 293, 294, 299
 - electron scattering, 303
 - electron storage ring, 526
 - electrostatic
 - charge, 306
 - chuck, 483, 489
 - discharge, 322
 - encoder, 211
 - energy deposition, 531
 - enhanced global alignment, 247, 254
 - equipment state, 463, 465
 - ESCAP, 79
 - etalons, 182
 - Etec Systems, 294
 - EV Group, 223
 - excimer lasers, 173, 175
 - ArF, 176, 183
 - KrF, 175, 181, 183
 - exposure, 2
 - field, 4
 - latitude, 29, 31, 32, 141
 - time, 459
 - extreme ultraviolet (EUV)
 - exposure system, 480
 - lens, 481, 483
 - light sensor, 485
 - light source, 493
 - lithography, 475, 479
 - requirements for mirrors, 498
- F**
- facilities cost, 470
 - FEN271, 314
 - FEP171, 313, 314
 - field curvature, 41, 135
 - field size, 459
 - flare, 197, 498
 - FLEX, 378
 - fly's eye, 186
 - focus, 33, 183
 - control, 43
 - drilling, 48
 - focus-latitude enhancement exposure, 48

- focused ion beam, 325
- fogging, 305
- forward scattering, 302, 303
- fragmentation, 364
- Fresnel-diffracted light, 219, 528
- FUJIFILM, 313
 - FEP-171, 533
- full-wafer scanner, 169
- fused silica, 193–195, 290, 432, 434

- G**
- gap, 528
- gas refills, 180
- Gaussian
 - beam, 302
 - system, 295
 - broadening, 302
 - round beam, 294
- GCA Corporation, 171
- GDSII, 307
- GHOST, 304
- gigaphoton, 184
- glass damage, 195
- global alignment, 254
 - enhanced, 247, 254
- gridded optical proximity correction, 364

- H**
- hammerhead, 359, 360
- hardbake, 2
- haze, 322
- HeNe laser, 209
- hexamethyldisilazane (HMDS), 57, 58
- hierarchy, 363
- high-index immersion fluid, 431
- HL-800D, 538
- Hopkins theory, 26
- hot plates, 69, 70, 86
- Huygen's principle, 124, 125

- I**
- illumination, 7, 19
 - conventional, 349
 - dipole, 349, 351
 - system, 185
 - uniformity, 185
- image
 - fading, 216, 217
 - log slope, 27, 29, 31, 32, 46, 367, 503
 - placement error, 488
- imaging, 7
- immersion
 - fluid, 420
 - lithography, 419, 420
- immiscible blocks, 544
- imprint lithography, 543
- IMS, 534
- incoherent light, 17
- individual depth-of-focus, 40, 42
- infrared aberration control system, 204
- injection locking, 183
- inspection, 2
 - die-to-database, 325
 - die-to-die, 324
- integral-squared pulse width, 178
- interfering plane waves, 12
- interferometric lithography, 447
- intrafield error, 259
- intrafield registration, 410
- inverse lithography, 382
- IPRO4, 306
- isodense bias, 355
- isofocal
 - dose, 43
 - points, 44

- J**
- JEOL, 296
- jerk, 214

- K**
- KTFR resist, 53

- L**
- labor cost, 470
- Lambert's law, 138

- laser-produced plasma, 494
 - source, 492
- leaching, 424
- Leica, 296, 533
- lens
 - aberration reduction, 439
 - distortion, 268
 - field curvature, 43
 - heating, 194, 203
 - placement error, 274
 - reduction, 4, 190
- lanthanum hexaboride, 294, 299
- laser ablation, 325
- leveling agents, 74
- light-intensity distribution, 7, 13, 45
- line-edge roughness (LER), 88, 400, 436, 502, 534
- line-end shortening, 360
- linewidth, 21
 - control, 16
 - measurement, 391
 - roughness, 400
- lithium, 493
- lithography simulations, 123
- lithography cost, 455, 458
- low k_1 , 437
- lutetium aluminum garnet, 432
- Lyman- α wavelength, 433
- M**
- Mack model, 159
- magnification error, 259
- maintenance cost, 469
- manufacturing electron-beam
 - exposure systems, 294, 299
- MAPPER, 534
- mask, 2, 169, 290
 - cost, 467
 - defect inspection, 324
 - defect printability, 327
 - deformation, 524
 - distortion, 292
 - nonflatness, 488
 - registration error, 289
 - roughness, 504
 - usage, 467
- mask-error factor, 365, 366, 368
- master oscillator power amplifier, 184
- matching error, 266
- mercury arc lamp, 173, 174
- metrology cost, 469
- Michelson interferometer, 209
- Micralign, 221, 223
- Micrascan, 174, 181, 200, 201
- Micronic Laser Systems, 312
- mirror reflectance, 479
- mirror-surface figure, 499
- mix-and-match, 264, 471
- Mo/Si
 - multilayer, 478
 - reflector, 477
- modeling, 123
 - programs, 128
- model, 123, 124, 126
- model-based optical proximity correction, 362
- modulation transfer function (MTF), 18, 357, 365
- Monte Carlo simulation, 303
- moving
 - average, 216
 - standard deviation, 216
- multi-electron-beam lithography, 534
- multilayer reflector, 476
- multilayer resist processes, 102
- multipass
 - gray, 300, 301
 - writing strategy, 316
- N**
- nanoimprint lithography, 543
- National Institute of Standards and Technology (NIST), 187, 396
- Nd-YAG laser, 494, 527
- negative resists, 2, 53, 54
- next-generation lithography, 523
- Nikon, 171, 173, 191, 199, 218, 252, 254

- nonconcentric field, 472
- nonconcentric matching, 276
- nonlinear overlay error, 257
- nonlinearity, 357
- nontelecentric lens, 262
- normalized
 - derivative, 29–32
 - image log slope, 33, 504
- NuFlare, 296
- numerical aperture, 15, 16
 - maximum, 430
- Nyquist frequency, 400
- O**
- OASIS, 307
- off-axis alignment, 249
- off-axis illumination, 190, 346, 349, 354, 378, 428
- Ohara, 193
- on-axis illumination, 346
- optical
 - contrast, 17, 19, 127
 - focusing, 208
 - raster scanning system, 310
 - superlattice, 375
 - vortex, 377
- optical-beam writer, 300
- optical lithography, 428, 441
- limits, 438
- optical-pattern generator, 292
- optical proximity correction, 356, 360
 - dense, 364
 - gridded, 364
 - model based, 362
 - sparse, 364
- optics contamination, 482
- optimum lens-reduction factor, 191
- optimum numerical aperture, 36
- outgassing, 483
- outrigger phase-shifting mask, 376
- over-priming, 59
- overexposed, 32
- overlay, 2, 241, 408
 - errors, 135, 410
 - measurement, 408
 - models, 255
- oxygen sensitivity, 53
- P**
- partial coherence, 36, 188, 189
- partially coherent light, 19
- pellicle, 317, 320, 491
 - standoff distance, 317
- Perkin–Elmer, 136, 221, 223, 532
- phase edge, 371
 - photomask, 372
- phase defect, 490
- phase error, 422
- phase-grating alignment, 249
- phase-measuring interferometry, 203
- phase shifting, 428
- phase-shifting mask, 368, 369
 - alternating, 370, 373, 378, 467
 - outrigger, 376
 - rim-shift, 376
- photoacid generators (PAGs), 72, 75, 138
- photoactive compound, 72, 74, 138
- photocluster, 458, 470
- photoelectron, 505
- photomask, 2, 289
 - blank, 289
- photorepeater, 169, 170, 289
- photoresist, 7, 53
 - sensitivity, 460
- pinholes, 66
- pitch, 18
- pixelated mask, 382
- planarize, 27
- PLASMASK, 104
- point x-ray source, 526
- poly(butene-1-sulfone) (PBS), 313
- poly(hydroxystyrene), 76
- polycapillary fiber, 528
- positive photoresists, 54
- positive resists, 2, 53–55, 77, 116
- post-exposure bake, 2, 147–149, 153

- power spectral density, 400
- prealignment
 - accuracy, 245
 - system, 244
- precision, 397
- pressure sensors for focusing, 208
- pressure-induced fluctuations, 211
- PREVAIL, 541
- priming, 57
- projection optical lithography, 544
- PROLITH, 127, 128, 145, 163
- proximity
 - correction, 304
 - effect, 302
 - printing, 169, 220, 222
- puddle development, 82
- pulse stretching, 178
- pulse-to-pulse repeatability, 181
- Q**
- quadrupole illumination, 190, 350, 351
- quantum efficiency, 140
- quantum yield, 506
- Quasar, 350
- queue, 465
- R**
- radation chemistry, 505
- rarefaction, 195
- raster scanning, 295
- Rayleigh
 - criterion, 16, 22, 35, 36, 129
 - depth-of-focus, 35
- reduction optics, 190
- reflectance, 479
- reflective notching, 156
- reflective optics, 136, 137, 199
- refraction, 39, 127
- refractive lens, 191
 - sensitivity to temperature and pressure, 201
- refractive optics, 136, 137
- registration, 242
- repetition rate, 177
- resist
 - coat, 1, 466
 - contrast, 25, 435
 - electron-beam-sensitive, 313
 - filtration, 64, 79, 80
 - sensitivity, 532, 534
- resist-edge slope, 20
- resolution, 10, 12, 15, 16, 19, 22, 36, 426, 430
 - enhancement techniques, 43, 345, 352, 428
 - unit of defocus, 35
- reticle, 169, 289, 290
 - Canary, 323
 - nonflatness, 291
 - registration error, 264
- rework, 468
- rim-shift phase-shifting mask, 376
- ring-field optics, 200, 501
- rotation factor, 257
- S**
- SAMPLE, 126–128
- sample charging, 393
- sampling, 272
- scale error, 257
- scaling laws, 428
- scanning, 215
- scanning electron microscope, 391, 392, 394
- SCALPEL, 539
- scattering bar, 359
- scatterometry, 402, 404
- Schott, 193, 497
- SEBN1637, 314
- secondary electron, 391
- self-assembly, 544
- self-calibration, 248
- self-vignetting, 499
- SEMI standard, 22
 - reticle format, 290
- SEMP9092, 314
- serifs, 358
- shaped beam, 296, 302, 533
- Shin-Etsu, 314

- shot noise, 502, 532, 534
 - Sigma7500, 312
 - silicon nitride, 142, 150
 - silicon oxynitride, 150
 - Silicon Valley Group (SVG), 223
 - skew, 260
 - slit height, 461
 - softbake, 2
 - solubility, 53
 - source-mask optimization, 380
 - spacer process, 444
 - spacing of elements, 202
 - sparse optical proximity correction, 364
 - spatial frequencies, 18
 - speckle, 184
 - spectroscopic ellipsometry, 402
 - spherical wave, 124, 125, 130, 131
 - spin coating, 60, 61, 68, 74
 - SRM 2069b, 396
 - SRM 2800, 396
 - stage-matching error, 267
 - stage precision, 210, 257
 - standby time, 464
 - standing wave, 143, 144, 147, 153, 155–157
 - static, 63
 - static dispense, 63
 - stencil mask, 541
 - step-and-repeat system, 3, 5, 186
 - step-and-scan, 203–205
 - system, 5, 186
 - model, 262
 - step-and-settle time, 459
 - stepper price, 456
 - stitching, 205
 - stochastic
 - beam blur, 535
 - scattering, 540
 - stress birefringence, 195
 - striations, 74
 - stripe boundary, 297
 - strong phase shifting, 374
 - subresolution feature, 359
 - suck-back, 65
 - Sumitomo NEB-33, 533
 - super-high-resolution illumination
 - control (SHRINC), 350
 - surface potential, 395
 - surfactants, 81
 - SUSS MicroTec, 223
 - Mask Aligner, 222
 - SVG Lithography, 174, 199
 - swelling, 53
 - swing curve, 145, 146
 - synchrotron, 492, 526
 - radiation, 526
- T**
- t-BOC, 77, 80
 - tandem stage, 218, 219
 - Teflon AF, 318
 - telecentric lens, 261
 - temperature-induced fluctuation, 211
 - TEMPEST, 127
 - template, 542
 - temporal pulse length, 178
 - tetramethyl ammonium hydroxide (TMAH), 73, 81, 83
 - thermal distortion, 531
 - thermal-field emission source, 294
 - thermionic emitter, 294
 - thick resist, 39
 - thin-film optical effects, 141
 - thin-resist model, 38, 43, 46
 - thorium, 175
 - three-beam imaging, 352
 - through-the-lens, 247, 249
 - alignment, 249, 251
 - throughput, 458, 460, 470, 531
 - tin, 493
 - titanium nitride (TiN), 142, 150, 153
 - tool-induced shift, 408
 - top-surface imaging (TSI), 104, 105
 - topcoats, 79
 - total-integrated energy (TRE), 173, 178
 - translation error, 256
 - trapezoid error, 261

trimethylsilyldiethylamine
(TMSDEA), 58
Twinscan, 218
two-beam imaging, 352
two-pass printing, 297
tyranny of the asymptote, 438

U

ULE, 497
Ultratech, 174
 Stepper, 171, 199
ultrathin resist, 66
underexposed, 32
usable depth-of-focus, 40, 42
utilization, 458, 463
UVIHS, 80, 85

V

vapor priming, 59
variable-shaped beam, 294
vector
 scanning, 295, 296
 system, 295
vector-shaped beam, 299
vibration, 214, 459
virtual addressing, 300
viscosity, 61–63, 65
Vistec, 534

W

wafer

 edge defects, 423
 expansion, 246
 heating, 537
 scaling, 257
 stage, 170, 209
 stepper, 3, 4, 169
wafer-induced shift, 409
water, 431
 temperature, 422
wavefront error, 131
wavelength, 16
working distance, 199
Wynne–Dyson design, 200

X

x-ray
 lithography, 523
 mask fabrication, 525
 source, 524
xenon, 492

Y

yaw, 213

Z

ZEP 7000, 314, 315
Zernike polynomials, 131, 132
zero-level alignment strategy, 250
Zerodur, 267, 497
zoom optics, 188



Harry J. Levinson is currently an independent consultant and Principal Lithographer of HJL Lithography. He has spent most of his career working in the field of lithography, starting at AMD. He also held positions at Sierra Semiconductor and IBM before returning to AMD in 1994. When wafer operations were spun off from AMD he moved to GLOBALFOUNDRIES and worked there until mid-2018. During the course of his career, Dr. Levinson has applied lithography to many different technologies, including bipolar

memories, 64-Mb and 256-Mb DRAM development, the manufacturing of application-specific integrated circuits, thin-film heads for magnetic recording, flash memory, and advanced logic. He was one of the first users of 5× steppers in Silicon Valley and was an early participant in 248-nm, 193-nm and EUV lithography.

Dr. Levinson served for several years as the chairman of the USA Lithography Technology Working Group that participated in the generation of the lithography chapter of the International Technology Roadmap for Semiconductors. He has published numerous articles on lithographic science, on topics ranging from thin-film optical effects and metrics for imaging, to overlay and process control, and he is the author of two books: *Lithography Process Control* and *Principles of Lithography*. He holds over 70 US patents. Dr. Levinson is an SPIE Fellow, previously chaired the SPIE Publications Committee, and served on SPIE's Board of Directors. In recognition of his contributions to SPIE, he received the Society's 2014 Directors' Award.

He has a B.S. in engineering from Cornell University and a Ph.D. in physics from the University of Pennsylvania. His Ph.D. thesis, titled "Resonances and Collective Effects in Photoemission," addressed certain phenomenon involving the interactions of light and matter. For this work he received the Wayne B. Nottingham Prize in surface science.