

Index

A

ABCD ray matrix, 46-54, 72-73, 116-172,
191, 205, 313-316, 341
and Huygens-Fresnel integral, 47, 341
table of, 47
Absorption (*see* atmospheric)
Aerosol scattering, 4
Airy disk, 347
Amplitude, 13, 74-75
fluctuations, 71-78
Angle-of-arrival, 28-29, 234
variance, 29
Anisoplanatism (*see* isoplanatic angle)
Aperture-averaging, 44-45, 167-199, 228-230,
313-318
beam wave, 189-195
factor, 44-45, 54, 167-168, 174, 182, 191,
212, 224, 229, 311-313, 358
plane wave, 45, 172-180
spherical wave, 180-189
Array,
detector, 226-234, 318-321, 328-332
(*see also* receiver)
Asymptotic theory, 38-41, 69, 98, 104, 128,
137, 153-155
Atmospheric,
absorption, 2, 4-5, 203, 211, 351
boundary layer, 2-4
coherence length, r_0 , 8, 10, 53, 223, 226,
312, 355, 358
scattering, 2, 4-5, 203, 211, 351
transmission, 4-5, 202, 350, 358, 366
spectrum (*see* power spectrum)
turbulence (*see* turbulence)
Attenuation, 4, 350, 358, 366
Average,
ensemble, 17, 21, 75
irradiance (*see* mean irradiance)

B

Background, 346
Backscatter amplification effect, 277, 288,
291-293, 295-300, 306
Bandwidth, 201, 207, 209, 217, 282
Beam
scintillation, 16 (*see also* scintillation index)

spreading, 15, 203, 212, 234, 284, 286,
359-360
wander, 16, 29-30, 152
wave (*see* Gaussian-beam wave)
Beam parameters, 11, 14-15, 33-34, 48-50,
55, 149, 169-170, 285-287, 313-316,
361-362
effective, 33-34, 151-152, 286-287
input plane (transmitter), 14, 49, 149, 169
output plane (receiver), 15, 49-50, 150-151,
170
Beam radius (spot size), 11, 14-15, 48, 149-
150, 169, 194, 341
effective (long term), 28, 30, 31, 151, 203,
205, 215, 246, 286
short term, 29-30
Beckman distribution (*see* lognormal-Rician
distribution)
Beer's law, 5
Bessel function, 18, 23, 88, 90, 111, 113, 116,
150, 170-171, 218, 236, 244, 245, 264-265,
271-272, 313
Binary transmission, 234-239
amplitude shift keying (ASK), 238-239
frequency shift keying (FSK), 238
on-off keying (OOK), 235-237
phase shift keying (PSK), 238
Bistatic
channel, 60, 283, 293-294, 300-303, 307,
321, 326
system, 277, 283, 316, 355
Bit, 234
Bit error-rate (BER), 234-239
Bump spectrum (*see* Hill spectrum and
modified atmospheric spectrum)

C

Carrier, 201
Carrier-to-noise ratio (CNR), 217, 219, 221-
225, 232, 312, 328-330, 358, 365
gain factor, 329
Cell (*see* eddy)
Channel, 54, 283
communication, 203
double-pass, 54, 277, 337
laser satellite, 257-273
terrestrial, 252-257

Chirp radar, 281
 Coherence, 16
 spatial, (*see* coherence radius)
 Coherence diameter (*see* atmospheric coherence length, r_0)
 Coherence radius, 16, 22, 25-27, 32-34, 38, 69, 82, 85-86, 202-203, 261, 286, 338, 359-360
 Gaussian-beam wave, 25, 32-34, 286
 plane wave, 26
 spherical wave, 26
 strong fluctuations, 32-34
 Coherent
 detector (*see* detector, coherent)
 imaging system, 340-345
 transfer function (CTF), 342, 344, 350
 Collecting lens (*see* lens)
 Communication system, 86-87, 201-239, 243
 laser satellite, 257-273
 Complex degree of coherence, 23, 26
 Complex phase perturbation, 17, 19, 79-80
 folded path, 277
 reciprocal path, 277
 Conditional density function, 212-213, 225-226, 244-245
 Confluent hypergeometric function, 28, 43, 53, 111, 113, 196, 265, 272
 Conformal transformation, 15
 Correlation
 between incident and reflected waves, 56-59, 277, 289, 304
 Correlation function
 amplitude enhancement, 56-59, 288
 Correlation width of irradiance fluctuations, 43, 110, 174, 176, 205, 266, 273, 287
 Covariance function of irradiance, 35, 42-44, 59, 97, 110-114, 138-139, 168, 195 264-266, 271-273, 291
 normalized, 43, 112, 167
 Cross-coherence function (*see* fourth-order moment)
 Crossings per second (*see* number of crossings)
 Cumulative probability density, 91, 246-247
 Current
 intermediate frequency, 215-218, 319-320
 noise, 206, 311
 signal, 206, 311

D

Decibel (dB), 212
 Delta function, 245, 247-248, 339

Demodulation, 201
 Detector, 203
 array, 226-234
 coherent, 203, 214-226, 248, 312-313, 358
 direct (incoherent), 203-214, 247, 311-312, 358
 envelope (*see* envelope detector)
 point, 205
 quantum efficiency, 206
 noise, 204, 235
 Diffraction
 angle, 71-72
 scattering, 71, 76
 Diffuse surface (*see* target, diffuse)
 Digital transmission, 234, 237
 Dissipation range, 6,
 Doppler
 frequency shift, 280-282
 radar, 278
 Double-pass propagation, 54-62, 277, 285, 288-290, 337
 Downlink path, 257-267

E

Earth's atmosphere, 2-4
 C_n^2 profile of, 8
 Echo signal (wave), 278
 Eddy, 6, 69, 71-78
 Electromagnetic spectrum, 202
 Electro-optic system, 337
 Energy cascade theory, 6
 Enhanced backscatter, 54, 277, 288, 291-293, 298-299, 306
 Ensemble average, 17, 21, 75
 Envelope detector, 217-220, 223-226, 358
 Equal gain (EG) receiver, 231-234, 318-331
 Error function, 208, 212, 235-236, 246, 311
 Expected number of fades (surges), 213, 243, 247-252
 Extended Huygens-Fresnel principle, 16, 19-21, 31
 Extinction coefficient, 5, 211, 280

F

Fade
 probability of, 209, 213, 225, 243-247, 252-255, 266, 273, 324-325, 330-332
 threshold parameter, 246, 266, 324, 331
 False alarm, 205
 rate (FAR), 209, 219, 221, 236
 (*see also* probability of)
 Far field, 27, 37, 279

Field of view (FOV), 279, 283, 342, 350
 Filter model, 83-84, 204, 259-260
 large-scale, 84, 99, 155, 162, 172
 low-pass, 217, 219, 223, 312
 small-scale, 84, 99, 155-156, 174
 Focal
 distance (eddy), 73
 plane, 195
 Focusing
 angle, 71-72
 regime, 38, 67, 77-78, 174
 Folded path, 277-278
 Fourier transform, 339
 convolution, 340
 inverse, 339
 Fourth-order moment, 17, 20-21, 59
 Fractional fade time (*see* probability of fade)
 Frequency
 filter cutoff, 84, 100-101, 106, 128-129,
 157, 160, 176, 261-262, 269-270, 348,
 351
 spatial, 53, 82-83, 342
 Frequency of
 fades and surges, 209-210, 213, 220-221
 Fresnel zone size, 30, 44, 69, 82, 110, 120,
 142, 174, 180, 198, 288
 Fried parameter (*see* atmospheric coherence
 length, r_0)
 Frozen turbulence hypothesis, 115, 195, 284

G

Gamma distribution, 88, 90, 244, 250-252,
 331
 joint (time derivative), 250-251
 Gamma function, 88, 219
 Gamma-gamma distribution, 89-92, 116-124,
 139-147, 236, 244, 247, 251-252, 324
 cumulative distribution, 91, 247
 joint (time derivative), 252
 parameters, 91, 120, 140, 237, 244, 324,
 327-328, 330-331
 Gaussian
 aperture, 53, 171, 233
 lens, 48-52, 205, 314, 342-343
 mirror, 54-55, 314
 Gaussian-beam wave, 11-13, 15-17, 48, 149,
 214, 283, 295, 341
 collimated, 13
 convergent, 13
 definition of, 11-13
 divergent, 13

fourth-order moment for, (*see* fourth-order
 moment)
 free-space irradiance for, 50, 205
 irradiance covariance function for
 (*see* covariance function of irradiance)
 lowest order (TEM₀₀), 11-13
 mean irradiance for (*see* mean irradiance)
 mutual coherence function for (*see* mutual
 coherence function, beam wave)
 parameters for (*see* beam parameters)
 scintillation index for (*see* scintillation
 index, beam wave)
 wave structure function for (*see* wave
 structure function, beam wave)
 Gaussian distribution, 79-80, 208, 210, 235,
 248
 joint (time derivative), 248
 Geometrical optics approximation, 29-30, 39,
 99-100, 110, 153, 190, 262
 Generalized hypergeometric
 function, 91, 139, 155, 247
 Geostationary orbit (GEO), 263, 266, 273
 Green's function,
 for Huygen-Fresnel integral, 13
 generalized, 47

H

Helmholtz equation, 16
 Heterodyne
 detection (*see* coherent detector)
 efficiency, 218
 Hill spectrum, 11
 Homodyne detection, 214
 Homogeneous and isotropic turbulence, 7, 18-
 19
 Hufnagle-Valley turbulence model, 8, 258, 266
 Huygens-Fresnel integral, 13
 extended, 16
 generalized, 47, 341
 Hypergeometric function, 36, 155,
 confluent, 28, 43, 53, 111, 113, 196, 265,
 272
 generalized, 91, 139, 155, 247

I

Image
 blurring, 350
 dancing, 16, 29
 plane, 52
 resolution, 348-350
 Imaging
 coherent system, 340-345

incoherent system, 346-354
 radar, 353-354
 Impulse response function, 338-339, 342, 344
 Index of refraction, 2
 fluctuations, 2, 6, 69-71
 inner scale for, 6
 outer scale for, 6
 profile model for, 8, 258
 structure constant, 2, 7-9, 67
 structure function, 7
 Inertial range, 6, 11, 32, 70
 Inner scale of turbulence, 6-9, 85-86, 104-107, 131-134, 158-161, 182-184, 192-194, 258
 Intensity (*see* irradiance)
 Intermediate frequency (IF), 214-218, 221-222
 signal current for, 215-218, 319-320
 Ionosphere, 3
 Irradiance, 50, 205, 211, 215, 222
 backscattered, 58, 288
 fluctuations, 2, 16, 67, 167-168, 211, 277
 (*see also* scintillation index)
 mean (*see* mean irradiance)
 moments, 35, 233
 Irradiance flux
 covariance, 170-171
 variance, 168, 172, 174, 176, 178, 182, 183, 185, 191, 193, 195, 318
 Isoplanatic angle, 8, 10
 Isotropic medium, 7
K
 K distribution, 87-89, 120-121
 Kolmogorov spectrum, 10, 70, 98, 128
 effective, 99, 128, 155
 Kummer function (*see* confluent hypergeometric function)
L
 Lambertian surface (*see* target, diffuse)
 Laser imaging radar, 353-354
 Laser radar, 277-278
 Lasercom (*see* communication system)
 Lens
 Gaussian model, 48-52, 205, 314, 342-343
 law, 170, 344
 Lidar (*see* laser radar)
 Linear
 combining methods, 231-234
 FM ranging, 282
 rectifier, 217, 219

 shift-invariant system, 338-341
 Local oscillator (LO), 214
 Log amplitude, 79, 87
 variance, 34, 75, 81
 Log-irradiance variance, 34, 81, 97, 127, 150, 155, 291-292
 Lognormal distribution, 80, 7, 120-121, 246, 248-250
 cumulative distribution, 246
 joint (time derivative), 249
 Lognormal-Rician distribution, 89, 141-146
 Longitudinal phase shift, 215
 Long-term beam spread, 28-30
 Low earth orbit (LEO), 263, 266, 273
 Low-pass filter, 217, 219, 223, 312

M

Marqum Q-function, 219, 238
 Maximal ratio (MR) receiver, 231
 Maximum unambiguous range, 280
 Maximum unambiguous velocity, 281
 Mean
 field, 17, 19-20
 signal current, 211
 signal power, 211
 Mean irradiance, 27-28, 222, 246
 double-pass, 58
 strong fluctuations, 31-32
 weak fluctuations, 27-28
 Mean fade time, 243, 255-257
 Mesosphere, 3
 Mie scattering, 4
 Missed detection (*see* probability of fade)
 Modified atmospheric spectrum, 11, 70, 104, 131, 175
 effective, 105, 132
 Modified Rytov theory, 79-81, 99, 128
 Modified von Kármán spectrum (*see* Von Kármán spectrum)
 Modulation, 201, 288, 309
 process, 79-82, 243-244, 289
 Modulation transfer function (MTF), 338, 346-355, 363-364
 aerosol, 351, 355
 atmospheric, 351-352, 355
 target, 364
 Moments,
 fourth-order, 17, 20-21, 59
 irradiance, 27-28, 31-32, 58, 87, 233
 mean field, 17, 19-20
 mutual coherence function (*see* mutual coherence function)

Monostatic
 channel, 54, 60, 283, 294-295, 303-305, 308, 318
 system, 277, 283, 357
 Mutual coherence function (MCF), 17, 20, 22-25, 31-34, 222, 286
 double-pass, 55-59, 361-362
 free space, 22
 Gaussian-beam wave, 22, 24
 plane wave, 23-24
 spherical wave, 23-24
 strong fluctuations, 31-34

N

Narrowband noise, 217, 234
 Near field, 37
 Negative exponential distribution, 88
 joint (time derivative), 250
 Noise,
 background, 204, 226
 current, 204, 206, 228
 electronic, 204
 power, 207, 211, 219, 312
 shot (detector), 204, 214
 Noncoherent detector (*see* detector, direct)
 Number of crossings (fades), 209, 213-214, 221, 226, 243, 247-252

O

On-off keying (OOK), 235-237
 Optical communications, 86-87, 201-239, 243, 257-273, 337
 Optical depth, 5
 Optical transfer function (OTF), 52-53, 338, 347
 Optical turbulence, 2, 5-10
 definition of, 7
 Outer scale of turbulence, 6-7, 86, 108, 135, 162, 177-178, 184-185, 194-195, 258

P

Passive scalar, 6
 Paraxial
 approximation, 13, 127, 149
 Perturbation method (*see* Rytov approximation)
 Phase
 longitudinal, 215
 perturbation, 79-80 (*see also* complex phase perturbation)
 structure function, 29, 38, 153-154, 259
 transfer function, 347

Phase front radius of curvature, 11, 14-15, 48, 149-152, 169, 341
 Photodetector (*see* detector)
 Photon noise-limited, 207
 Pixel, 357
 SNR for, 357-359, 364-367
 Plane wave, 97
 covariance function, 43, 111, 113
 mutual coherence function, 23-24
 scintillation index, 36, 39-40, 101, 104, 107, 109
 structure function, 23-24, 40
 Point
 detector, 205, 318
 reflector (*see* target, point)
 source (*see* spherical wave)
 Point spread function (PSF), 52, 338, 346-348
 Poisson statistics, 208
 Power, 167, 206, 211
 detector (*see* detector, direct)
 local oscillator (LO), 215
 fluctuations, 167, 228, 244
 mean, 167, 311
 signal, 206, 211, 215, 311, 329
 noise, 207, 211
 Power spectral density (*see* power spectrum)
 Power spectrum, 10-11
 effective, 99, 105, 128, 132, 155
 Hill spectrum, 11
 Kolmogorov, 10, 70, 98, 128
 modified atmospheric, 11, 70, 104, 131
 Tatarskii, 11, 70
 von Kármán, 11, 163
 Probability density function, 86-92
 Gamma distribution, 88, 90, 244, 250-251, 331
 Gamma-gamma distribution, 89-92, 116-124, 139-147, 236, 244, 247, 251-252, 324
 Gaussian distribution, 208, 210, 248
 K distribution, 87-89, 120-121
 lognormal distribution, 87, 120-121, 246, 248-250
 lognormal-Rician distribution, 89, 141-146
 negative exponential distribution, 88
 Rayleigh distribution, 218
 Rician distribution, 218
 Probability
 of detection, 207-208, 243, 311-313
 of fade, 209, 213, 225, 243-247, 252-255, 266, 273, 324-325, 330-332

of false alarm, 207-208, 311, 313
 of error (*see* bit error-rate)
 Propagation
 ABCD optical system (*see* *ABCD* ray matrix)
 double-pass, 54-62, 277, 337
 parameter, 13
 Pulse
 Doppler radar, 278
 repetition interval, 278
 repetition frequency, 278
 delay ranging, 280
 length, 281
 Pulse compression techniques, 281-282
Q
 Quantum efficiency, 206
 Quasifrequency, 210, 221, 249, 251
R
 Radar, 219, 278-283
 (*see also* laser radar)
 Random medium, 14, 68
 Range
 equation, 279
 rate, 280
 resolution, 281
 Ray matrix (*see* *ABCD* ray matrix)
 Rayleigh
 criterion, 348-349
 distribution, 218, 231, 238
 scattering, 4
 Receiver
 beam parameters (*see* beam parameters,
 receiver)
 spatial diversity, 226-234
 (*see also* detector)
 Reciprocal path, 277-278
 Reflector (*see* target)
 Refractive index (*see* index of refraction)
 Refractive scattering, 71, 76
 Resolution, 337, 348-350
 range (*see* range resolution)
 Rice-Nakagami distribution (*see* Rician
 distribution)
 Rician distribution, 218, 238
 Rytov approximation, 16-19, 79, 97-98
 modified, 79-81, 99
 statistical moments of, 17-18
 Rytov variance, 1, 36
 for beam wave, 155, 157
 for plane wave, 1, 36, 67, 98, 128, 130,
 260, 286, 323, 327

for spherical wave, 36, 130
S
 Satellite laser communication system, 257-
 273
 Saturation regime, 38, 67-69, 77, 98, 153
 Scattering disk, 71, 82, 174, 198
 Scattering
 aerosol, 4
 Mie, 4
 Rayleigh, 4
 Scintillation index, 34-41, 53, 67-69, 81-82,
 97, 128-129, 150
 double-pass, 59-62, 288-290, 293-295,
 300-305, 306-310, 322-323, 326, 330,
 355-357, 364
 downlink channel, 260-264
 Gaussian-beam wave, 36-37, 157, 159, 160,
 162, 287
 large-scale, 82, 100, 106, 129, 132, 140-
 141, 156, 160, 162, 262-263, 269-270
 longitudinal component, 36, 150
 plane wave, 36, 39-40, 101, 104, 107,
 109, 263
 radial component, 36, 150, 152
 residual, 317
 small-scale, 82, 101, 107, 130, 133, 140-
 141, 156, 261, 268-269
 spherical wave, 36, 39, 41, 53, 130, 133,
 135, 270
 strong fluctuations, 38-41, 98, 104, 128
 uplink channel, 268-273
 weak fluctuations, 35-38
 Seeing, 337, 353
 Signal
 current, 206, 215-218
 intermediate (IF), (*see* intermediate
 frequency)
 power, 206, 211, 215, 311, 329
 Signal-to-noise ratio (SNR), 203, 205, 207,
 212, 219-220, 224, 228, 311, 312, 338,
 350, 365
 single pixel, 357-359, 364-367
 Soft aperture (*see* Gaussian aperture)
 Spatial coherence radius (*see* coherence radius)
 Speckle, 318-319, 362
 reflection coefficient, 361
 size, 363
 target, 318, 326, 331, 338, 350, 362, 365
 Spectrum (*see* power spectrum),
 electromagnetic, 202
 temporal (*see* temporal spectrum)

Spherical wave, 16, 25, 127, 171, 180, 268, 290, 306, 355, 364
 covariance function, 43
 mutual coherence function, 23-24
 scintillation index, 36, 39, 41, 53, 130, 133, 135, 270, 294
 structure function, 23-24
 Spot size (*see* beam radius)
 Square-law device, 217, 219, 223, 312
 Stratosphere, 3
 Strehl ratio, 53, 212
 Strong fluctuations, 2, 16, 71, 77, 82, 179-180, 189, 286, 289
 Structure constant, 2, 7-10, 16, 67, 71, 77, 82
 Hufnagle-Valley model for, 8, 258, 266
 Structure function,
 index of refraction, 4
 phase (*see* phase, structure function)
 wave (*see* wave structure function)
 Structure parameter (*see* structure constant)
 System function (*see* transfer function)

T

Target
 classification, 282-283
 definition of, 346
 Diffuse (Lambert), 54, 58, 60, 279, 282, 306-310, 319, 326-332, 354, 359-367
 Gaussian, 54-55, 283, 285
 point, 54, 56, 59, 282, 290-305, 317, 319, 321-326
 resolved, 283
 smooth, 314
 specular, 282, 285, 354
 speckle, 318, 326, 331, 338, 350, 365-366
 statistical model for, 360-363
 unresolved, 282-283, 290-305, 354-359
 Tatarskii spectrum, 11, 70
 Taylor frozen turbulence hypothesis, 115, 195, 284
 Temporal spectrum, 115-116, 195-199, 248
 Terrestrial link, 252-257
 Thermosphere, 3
 Threshold, 205, 208, 219, 244-245
 detection, 205-209, 211-226, 311-317
 fade parameter, 246, 266, 324, 331
 -to-noise ratio (TNR), 209, 238
 Tilt, 350, 360
 Transceiver, 54, 277, 283
 Transfer function, 338, 340
 Transmittance, 4-5, 350, 358, 366

Transmitter beam parameters (*see* beam parameters, transmitter)
 Tropopause, 3
 Troposphere, 3
 Turbulence, 6, 203
 cascade theory, 6
 dissipation range, 6
 eddy, 6, 71-78
 inertial range, 6, 11, 70
 inner scale (*see* inner scale of turbulence)
 Kolmogorov theory, 6
 outer scale (*see* outer scale of turbulence)
 Two-thirds law, 7

U

Uplink path, 268-273

V

Variance,
 of angle-of-arrival fluctuations, 29
 of log-amplitude fluctuations, 34, 75, 81, 97, 127
 von Kármán spectrum, 11, 163

W

Wander (*see* beam wander)
 Wave equation, 16
 Wavefront radius of curvature (*see* phase front radius of curvature)
 Wave number, 2, 67
 Wave structure function,
 Gaussian-beam wave, 23
 plane wave, 23-24, 222
 spherical wave, 23-24, 56
 Wavelength, 2, 67
 Weak fluctuations, 2, 16, 76, 82, 174, 179, 188, 286, 288, 356

Z

Zenith angle, 258
 Zero crossings (*see* frequency of fade *and* number of crossings)



Larry C. Andrews is a professor of mathematics at the University of Central Florida, an associate member of the School of Optics/CREOL, and an associate member of the Florida Space Institute (FSI). Previously, he held a faculty position at Tri-State University and was a staff mathematician with the Magnavox Company, antisubmarine warfare (ASW) operation. He received a doctoral degree in theoretical mechanics in 1970 from Michigan State University. Dr. Andrews has been an active researcher in optical wave propagation through random media for over 20 years and is the sole or principal author of several mathematics textbooks: differential equations, boundary value problems, special functions, and integral transforms. He is also coauthor of the textbook *Laser Beam Propagation through Random Media* (SPIE Press, 1998). Along with wave propagation through

random media, his research interests include special functions, random variables, atmospheric turbulence, and signal processing.



Ronald L. Phillips is Director of the Florida Space Institute (FSI) and a professor in the School of Electrical Engineering and Computer Science at the University of Central Florida. Dr. Phillips is also a member of the Department of Mathematics and an associate member of the School of Optics/CREOL. He has held positions on the faculties at Arizona State University and the University of California, San Diego. He received a doctoral degree in Electrical Engineering in 1970 from Arizona State University. Dr. Phillips has been an active researcher in wave propagation through random media for more than 25 years. He was awarded a Senior NATO Postdoctoral Fellow in 1977 and the American Society for Engineering Education 1983 Medal for outstanding contributions in research. Dr. Phillips is coauthor of the textbook *Laser Beam Propagation through Random Media* (SPIE

Press, 1998). In addition to optical wave propagation, his research interests include optical communications and imaging through atmospheric turbulence.



Cynthia Y. Hopen is a Professor of Mathematics and a Research Scientist for the Florida Space Institute at the University of Central Florida. She holds a B.A. in Mathematics Education from the University of North Carolina, M.S. in Mathematical Science from the University of Central Florida, and M.S. in Electrical Engineering and Ph.D. in Applied Mathematics from the University of Washington, Seattle, WA. Dr. Hopen was awarded a National Physical Science Consortium doctoral fellowship with the Kennedy Space Center (KSC) as her sponsor. She has worked with chemists in the Material Science Division and physicists in the Optics Lab at KSC. In 1997 she joined the faculty at FSI/UCF where she presently is doing research in the area of laser communications and laser radar. She has worked on laser satellite communication projects through the Navy

and laser radar projects for the Air Force. In 2001 she was awarded the Young Investigator Award from the Office of Naval Research.